

MODEL

12266DLD



1200 DOUBLE MONITORED MAGLOCK 12/24 VDC

1200 double monitored electromagnetic lock designed for indoor access control applications requiring a 545 kg holding force. Equipped with LED lock status indication and relay outputs for remote signalling.

CE certified and manufactured under strict quality control.



Life Safety
Applications



Zero Residual
Magnetism



Low Energy
Consumption



12/24 VDC
Selectable



MOV Surge &
Spike Protection

SPECIFICATIONS


	Holding Force	Up to 1200lbs (545kg)
	Lock Status Monitoring	Yes (LED Indicator)
	Current / Voltage	12VDC : 480mA ±10% 24VDC : 240mA ±10%
	EST Weight	9.6kg approx
	Housing	Anodized Aluminium
	Operating Temperature	-10 ~ +55° C
	Operating Humidity	0~95% (non condensing)

DIMENSIONS (mm)


CODE: 12266DLD

	Maglock Size (L × W × H)	532 × 76 × 40 mm
	Armature Plate Size (L × W × H)	185 × 61 × 16 mm x 2

MAGLOCK



ARMATURE PLATE



Note: All dimensions are in millimetres (mm). Dimensions shown are nominal. Unless otherwise specified, a manufacturing tolerance of ±0.5 mm applies.

RELATED PRODUCTS



ESI Access Sdn Bhd

24, Jalan Industri USJ 1/12, Taman Perindustrian
USJ 1, 47610 Subang Jaya, Selangor, Malaysia.

+603 8024 9318

sales@esi-access.com

www.esi-access.com



AGM10327